

Your Application's Parameters					Rebling Terminal Selection Guide				Accessories												
Rated Current	Your Panel Material	Your Panel Thickness (inches)	Desired Panel Mounting Pattern	Connector Plating	Style	Insulator Color	P/N 1 pc/ bag	Advantages over other Styles	O-ring	Gasket	Flexible Cover	Long Rigid Cover	Short Rigid Cover								
250 amps	Plastic	0.025→0.220 (0,635→5,6 mm)	3 circular holes	Unplated Brass	SFT	Black	RBL-SFT-B-B	Can be mounted on very thin or weak panels Mounting holes can be made with a hand drill	-	RBL-716A1814											
				Ni-plated Brass		Red	RBL-SFT-B-R														
		0.230→0.660 (5,84→16,76 mm)	1 double-D hole	Unplated Brass	LFT	Black	RBL-LFT-B-B							Smallest Footprint, Lowest Cost Simplest Environmental Seal	RBL-700A1799	-					
				Ni-plated Brass		Red	RBL-LFT-B-R														
			3 circular holes	Unplated Brass	SFT	Black	RBL-SFT-B-B														
				Ni-plated Brass		Red	RBL-SFT-B-R														
	Metal	0.025→0.100 (0,635→2,54 mm)	3 circular holes	Unplated Brass	SFT	Black	RBL-SFT-B-B	Can be mounted on very thin or weak panels Mounting holes can be made with a hand drill	-	RBL-716A1814	RBL-713A1806-B (BLK) RBL-713A1806-R (RED) RBL-713A1806-E (BLU)	RBL-698A1789-L-B (BLK) RBL-698A1789-L-R (RED) RBL-698A1789-L-E (BLU)	Note: maximum cable section 2 AWG (35 mm ²)	RBL-698A1789-S-B (BLK) RBL-698A1789-S-R (RED) RBL-698A1789-S-E (BLU)							
				Ni-plated Brass		Red	RBL-SFT-B-R														
		0.110→0.660 (2,79→16,76 mm)	1 double-D hole	Unplated Brass	LFT	Black	RBL-LFT-B-B								Smallest Footprint, Lowest Cost Simplest Environmental Seal	RBL-700A1799	-				
				Ni-plated Brass		Red	RBL-LFT-B-R														
			3 circular holes	Unplated Brass	SFT	Black	RBL-SFT-B-B														
				Ni-plated Brass		Red	RBL-SFT-B-R														
500 amps	Plastic or Metal	0.025→0.660 (0,635→16,76 mm)	3 circular holes	Unplated Brass	MFT	Black	RBL-MFT-B-B	Can be mounted on very thin or weak panels Mounting holes can be made with a hand drill	-	RBL-716A1815											
				Ni-plated Brass		Red	RBL-MFT-B-R														
750 amps	Plastic	0.025→0.180 (0,635→4,57 mm)	3 circular holes	Ni-plated Brass	XFT	Black	RBL-XFT-P-B	Can be mounted on very thin or weak panels Mounting holes can be made with a hand drill		RBL-720A1817											
				Ni-plated Brass		Red	RBL-XFT-P-R														
	Plastic	0.190→0.550 (4,83→13,97 mm)	1 double-D hole	Ni-plated Brass	BFT	Black	RBL-BFT-P-B	Smallest Footprint, Lowest Cost Simplest Environmental Seal		RBL-651A1811			RBL-648A1758 (BLK) RBL-648A1779 (RED)								
				Ni-plated Brass		Red	RBL-BFT-P-R														
	Metal	0.025→0.070 (0,635→1,78 mm)	3 circular holes	Ni-plated Brass	XFT	Black	RBL-XFT-P-B	Can be mounted on very thin or weak panels Mounting holes can be made with a hand drill		RBL-720A1817											
				Ni-plated Brass		Red	RBL-XFT-P-R														
		0.080→0.550 (2,03→13,97 mm)	1 double-D hole	Ni-plated Brass	BFT	Black	RBL-BFT-P-B	Smallest Footprint, Lowest Cost Simplest Environmental Seal		RBL-651A1811			RBL-648A1758 (BLK) RBL-648A1779 (RED)								
				Ni-plated Brass		Red	RBL-BFT-P-R														
1000 amps	Plastic	0.025→0.180 (0,635→4,57 mm)	3 circular holes	Ni-plated Copper	XFT	Black	RBL-XFT-N-B	Can be mounted on very thin or weak panels Mounting holes can be made with a hand drill		RBL-720A1817	RBL-639A1830-B (BLK) RBL-639A1830-R (RED)										
				Ni-plated Copper		Red	RBL-XFT-N-R														
		0.190→0.550 (4,83→13,97 mm)	1 double-D hole	Ni-plated Copper	BFT	Black	RBL-BFT-N-B	Smallest Footprint, Lowest Cost Simplest Environmental Seal		RBL-651A1811			RBL-648A1758 (BLK) RBL-648A1779 (RED)								
				Ni-plated Copper		Red	RBL-BFT-N-R														
	Metal	0.025→0.070 (0,635→1,78 mm)	3 circular holes	Ni-plated Copper	XFT	Black	RBL-XFT-N-B	Can be mounted on very thin or weak panels Mounting holes can be made with a hand drill		RBL-720A1817											
				Ni-plated Copper		Red	RBL-XFT-N-R														
		0.080→0.550 (2,03→13,97 mm)	1 double-D hole	Ni-plated Copper	BFT	Black	RBL-BFT-N-B	Smallest Footprint, Lowest Cost Simplest Environmental Seal		RBL-651A1811			RBL-648A1758 (BLK) RBL-648A1779 (RED)								
				Ni-plated Copper		Red	RBL-BFT-N-R														
			3 circular holes	Ni-plated Copper	XFT	Black	RBL-XFT-N-B	Mounting holes can be made with a hand drill		RBL-720A1817											